

SIMPLY COLOUR PREMIUM MATT

CODE:	SCP
DESCRIPTION:	Simply Colour Premium Matt is a unique anti-bacterial paint with the patented IONACTIVE™ ingredient that prevents the growth of most types of unhealthy bacteria, mould and mildews. IONACTIVE™ begins to work immediately and lasts the lifetime of the paint.
PRODUCT BENEFITS:	Washable anti-bacterial paint, Eco-friendly, Zero VOC, Lead free, Zero solvents and Low odour. Suitable for use in Nurseries, Hospitals, Clinics, Hotel Rooms, Abattoirs and Green Buildings, because of its unique formulation.
SURFACE PREPARATION:	Loose flaking paint and efflorescence must be completely removed. All bare exposed metal areas must be spot primed with the appropriate primer and undercoat. Gloss/oil paint surfaces to be thoroughly sanded and wiped down with damp cloth. Chalky surfaces must be thoroughly sanded before applying a Water Based VOC-Free Plaster Primer.
PRECAUTIONS:	Do not apply during cold, wet conditions. Do not apply directly to unprimed metal surfaces.
APPLICATION:	Stir thoroughly with flat paddle before use. Ready for use by brush, roller and airless spray. Allow 2 hours @ 25°C drying in between coats. Apply a minimum of 2 coats. Thinning not normally necessary. Clean up with water.
TECHNICAL DATA:	
SG:	1.44 +/- 0.02
Drying Time: (T) @ 25°C (H):	2 hours 4 hours
Recoat:	4 hours
Finish:	Very low sheen
Viscosity:	105 - 110 KU
Solids Mass:	56 - 58%
Spread Rate:	Approx. 8 - 10m ² /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	White & Tint Bases
Pack Size:	5L
Scrubs:	> 10 000
Gloss @85°:	< 10%
Health and Safety:	Refer to Material Safety Data Sheet

SIMPLY COLOUR MATT PVA

CODE: DTM02

Description: A high quality low VOC, low odour, matt washable finish for interior and exterior use.

Product Benefits: Provides a high opacity. Provides excellent interior/exterior durability.

SURFACE PREPARATION:
New Work:

1. Concrete and plaster surfaces must be primed with Simply Colour Plaster Primer.
2. Wooden surfaces must be primed.
3. Metal surfaces must be primed with a suitable primer.

New Work:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed.

GENERAL:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler.
3. Consult our sales staff for application onto any other substrate.

APPLICATION: Application by brush, roller or airless spray. Apply 2 coats. Thinning not normally necessary. Clean up with clean water.

TECHNICAL DATA:

SG:	1.45 +/- 0.05
Drying Time: (T)	40 minutes
Drying Time: (H)	24 hours
Overcoat:	2 hours
Solids Mass:	50 - 55%
Finish:	White Matt. Bases very Matt
Viscosity:	95 - 100 KU
Spread Rate:	Approx 8 - 10m ² /lt depending on surface profile and porosity.
Scrubs:	10 000
Colour Range:	White Bases: Pastel, Deep, Transparent

Note: Certain transparent colours may require a minimum of 3 coats to achieve total obliteration.

SIMPLY COLOUR PLASTER PRIMER

CODE:	SCR 01
DESCRIPTION:	Specifically recommended as a primer for surfaces to be top coated with Simply Colour Premium Matt. Suitable as a primer/sealer for penetrating and binding powdery surfaces. i.e. distemper and chalky PVA on inferior surfaces. Excellent ZERO VOC sealer.
PRODUCT BENEFITS:	A zero VOC (<1g/l), environmentally friendly plaster primer. Exhibits good alkali resistance with good sealing properties. Both a primer and a sealer. Quick Drying. Green standard status if used in conjunction with Simply Colour Premium Matt.
SURFACE PREPARATION:	All surfaces must be clean, dry and free from all foreign contaminants. New plaster must have a moisture content below 10% before application. Powdery, chalky surfaces must be thoroughly wire-brushed/sanded. All loose and flaking paint to be removed.
GENERAL:	Not to be used as a primer on metal. Masonry surfaces must be dry before applying this material. Moisture content not to exceed 10% on moisture meter.
APPLICATION:	Stir thoroughly with flat paddle before use. Ready for use by brush or roller. Brush application preferred. Thin if required with clean water. Thin only when overcoating chalky and very porous surfaces. Clean up with water.
TECHNICAL DATA:	
Type:	Water based
Drying Time: (T)	2 Hour
@ 25°C (H):	8 Hours
Recoat:	6 Hours
Viscosity:	80 - 85 KU
SG:	1.21 - 1.23
Solids by Volume:	30-34%
Spread rate:	Approx. 6m ² /L depending on surface porosity.
Solids by Mass:	44 - 48%
Finish:	Low Sheen
Colour Range:	White
Pack Sizes:	5lt
Health and Safety:	Refer to Material Safety Data Sheet

SIMPLY COLOUR TRIM

CODE:	SGL
DESCRIPTION:	Waterbased Simply Colour Trim is a premium quality enamel with a satin finish. Can be used on new or previously painted surfaces such as doors, window frames, cupboards, skirting boards, furniture and walls.
PRODUCT BENEFITS:	Very convenient. Quick drying. Dries to an attractive, tough, washable sheen finish. Equipment easily cleaned in water. Superior, non-yellowing trim paint for interior/exterior use. Low odour and mould resistant.
SURFACE PREPARATION:	Loose flaking paint and efflorescence must be completely removed. All bare exposed metal areas must be spot primed with the appropriate primer and undercoat. Gloss/oil paint surfaces to be thoroughly sanded and wiped down with damp cloth. Chalky surfaces must be thoroughly sanded before applying Dekade Surface Conditioner. Kitchen walls without exception to be washed down with sugar soap and water.
PRECAUTIONS:	Do not apply during cold, wet conditions. Do not apply directly to unprimed metal surfaces. Not recommended for high moisture areas.
APPLICATION:	Brush application preferred. A minimum of 2 coats is required for best results. Do not dilute. Clean up with water.
TECHNICAL DATA:	
Type:	Acrylic copolymer.
SG:	1.22 - 1.25
Drying Time: (T) @ 25°C (H):	2 hour 8 hours
Recoat:	4 hours
Full Cure:	7 days
Finish:	Sheen
Viscosity:	110 KU
Solids Mass:	47 - 50%
Spread Rate:	Approx. 8 - 10m ² /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	White, Pastel and Deep Bases
Pack Size:	1L & 5L
Health and Safety:	Refer to Material Safety Data Sheet